PACIFIC TRINETICS
CORPORATION

PTC BLANKER



- 마일라 필름에 코팅된 녹색 세라믹 테이프를 자르기 위한 용도
- 고속 릴투시트 블랭킹
- 가장자리 다듬기 유무에 따른 비교 고속
- 바코드/QR 코드 인쇄 가능
- 선택 사항인 자동 시각 검사

PTC 블랭커

BA 시리즈 세라믹 블랭킹 시스템은 다음과 같이 설계되었습니다. 세라믹 롤의 고속 정밀 절단용
마일라 필름을 테이프로 붙여 시트 형태로 자릅니다. 길이와 너비 방향으로 자릅니다. 완전히 조절 가능하며 다양한 종류의 테이프가 있습니다.
다양한 두께를 수용할 수 있습니다.

향상된 소프트웨어와 직접 구동 방식을 갖추고 있습니다.
시스템과 최첨단 장력 제어
시스템에서 미리 프로그래밍된 레시피는 다음과 같이 호출됩니다. 정확한 위치 지정을 통한 블랭킹 위치
타이밍.

다양한 출력 구성이 가능합니다.
재단된 판재들을 대량 또는 개별적으로 모아 놓은 컬렉션입니다. 분리 가능한 카세트가 담긴 선반에 구분되어 있습니다.
PTC 블랭커는 고급 정전기 제거기도 제공합니다.
또한 용지 추적을 위한 바코드 인쇄 기능도 있습니다.
.

주요 기능 개요

- 고속 절단
- 고정밀 블랭킹
- 자동 장력 및 속도 조절 제어
- 인라인 자동 검사 테이프 품질
- 바코드/QR 코드 인
- 쇄 정전기 제거
- OPC- UA 데이터 통신



모델: BA06001

MODELS

BA06001

BA08001

BA10001

SPECIFICATIONS

FEATURES	BA06001	BA08001	BA10001
Max. tape Width	6"	8"	10"
Max. cut length	Adjustable 0 – 10" (254mm), 0.1" (2.54mm) increments		
Max # of cuts / sec	5 (depends on cut length)	5 (depends on cut length)	1 (depends on cut length)
Control System	PLC	PLC	PC - PLC
Dimensions L x W x H (mm)	1600 x 700 x 1400	1650 x 750 x 1400	3750 x 1770 x 1650

FACILITIES REQUIREMENTS

FEATURES	BA06001	BA08001	BA10001
Electrical	230VAC+/-5%, 50Hz, 500W	230VAC+/-5%, 50Hz, 500W	380VAC, 20AMPS. Phase 3. Freq. 50/60Hz
Compressed Air	100psi (7kg/cm2)	100psi (7kg/cm2)	100psi (7kg/cm2)