PACIFIC TRINETICS
CORPORATION

TAPE CASTER

Compact



- Compact, proven design
- Offered in standard and long version
- Best for R&D and pilot-scale production
- Max cast tape widths of 6" and 8" (AT06001 / AT08001)
- Individually controlled heaters

Dimensions: L x W x H (mm)

	STD	LONG
AT06001	1.9m x 1m x 1.6m	2.3m x 1m x 1.6m
AT08001	1.9m x 1m x 1.6m	2.3m x 1m x 1.6m

Cast tape thickness range*

	STD	LONG
AT06001	7.5-200uM	7.5-225 uM
AT08001	7.5-200 uM	7.5-225 uM

*Higher thickness maybe available.
Contact sales@ptchips.com for more details.

PTC 테이프 캐스터 (콤팩트)

PTC 컴팩트 테이프 캐스터는 다음과 같은 용도에 완벽한 선택입니다. 실험실 및 시범 규모 생산에 적합합니다. 다음과 같은 기능을 제공합니다. 사용자 친화적인 인터페이스를 유지하면서
다양한 연구를 위한 정교한 플랫폼
시범 생산 규모.

AT 시리즈 디자인은 검증된 실적을 보유하고 있습니다.
신뢰성과 내구성이 뛰어납니다. 게다가 크기도 작습니다.
풋프린트는 최소한의 공간 점유를 보장합니다.
최상급 클린룸 환경.

이 시스템은 여러 개의 개별적으로 제어되는 기능을 갖추고 있습니다. 마일라 아래에 발열 패드를 넣어 유연성을 확보했습니다.
다양한 슬러리에 대한 습식 주조 테이프 건조
제형. 정밀한 닥터 블레이드는 다음을 보장
합니다. 일정한 두께와 고품질의 테이프.

주조는 일반적인 수직 닥터를 사용하여 수행됩니다. 입력부에 위치한 화강암 표면 플레이트 위의 블레이드 테이프 캐스터의 끝부분.

개요

- 컴팩트하고 사용하기 편리합니다
- 믿을 수 있고 내구성이 뛰어납니다
- 작은 면적
- 개별 제어식 난방 패드
- 정밀 의사용 칼날
- 연구 개발 및 시범 운영에 가장 적합합니다. 생산
- 표준형과 긴형으로 제공됩니다. 버전
- 최대 캐스트 테이프 너비는 6인치입니다. 8인치 (AT06001 / AT 08001)



모델: AT 08001

명세서

캐스트 테이프 두께 범위	7.5-200µM | 7.5-225µM
정확성	+/- 1 µM ± 10% 중 더 큰 값
캐스트 테이프 너비	152mm(6인치) 및 203mm(8인치)
건조 온도	최대 100°C
속도	100~1,500mm/분
마일라 폭	6인치 캐스트 테이프는 200mm, 8인치 캐스트 테이프는 230mm입니다.

유용

입력 전압	220V 3상 35A
압축 공기	100 psi > 5 CFM

옵션

비접촉식 습식 또는 건식 두께 측정 기능과 같은 옵션의 경우,

sales@ptchips.com 으로 문의하세요.